



TV Portal +

Web Browser with Live TV (BIP)

Stylish icon menu



SPECIFICATION

* Tuner & Channel Decoder (Satellite)

Input Connector	F-type, IEC 169-24, Female
Loop through out	F-type, IEC 169-24, Female
Frequency Range	950MHz ~ 2150MHz
Input Impedance	75Ω, unbalanced
Signal Level	-65 to -25dBm
LNB Power	13/18VDC, max.400mA
22KHz Tone	(22±2)KHz, (0.7±0.2)V
DISEqC Control	V1.0/1.2/USALS Compatible
Demodulation	QPSK / 8PSK
Input Symbol Rate	1 ~ 45 Ms/s (QPSK of DVB-S) 1 ~ 45 Ms/s (QPSK of DVB-S2)
FEC Decoder	1/2,3/5, 2/3, 3/4, 4/5,5/6,8/9,9/10 and 7/8 (QPSK) 3/5, 2/3, 3/4, 5/6, 8/9 and 9/10 (8PSK)

* MPEG Transport Stream A/V Decoding

Transport Stream	MPEG-4 part 10(H.264), MPEG-2, VC-1/WMV9, HD or SD video decoding
Profile Level	Decoding of 1080p/60 AVC@L4.2, Dual HD AVC@L4.1 and MVC SHP@L4.1 video stream 3DTV decoding and display
Input Rate	Max. 480Mbit/s
Video Formats	4:3 LetterBox, 4:3 PanScan, 16:9
Video Resolution	720x576i, 720x576p, 720x480i, 720x480p, 1280x720p, 1920x1080i, 1920x1080p
Audio Decoding	MPEG1 I/II, MP3, Dolby Digital/DD+/Pulse, MPEG4 AAC/AAC+
Audio Mode	Stereo/Joint stereo/Mono, Dolby AC3
Sampling Rate	32KHz, 44.1KHz and 48KHz

* Main System

Main Processor	Sti Chipset
Memory	Flash-ROM : 256 MBytes SDRAM : 512 MBytes (DDR3) EEPROM : 256 Bytes

* Physical Specification

Size (W x H x D)	300mm X 60mm X 230mm
Weight (Net)	2 Kg(w/o HDD)
Operating Temp.	0°C ~ +45°C
Storage Temp.	-10°C ~ +70°C



Size (W x H x D) : 300mm X 60mm X 230mm